

morleys

ADHESIVES

JM500 Acrylic Adhesive

Uniclass L5391:L673	EPIC E4:F73
Cl/SfB (43) Yt3	

JM500 is a SOLVENT FREE acrylic emulsion based adhesive. This easy to spread adhesive, with long open time, provides early tack and minimum slip, quickly building to a strong permanent bond. It is non-staining, has excellent resistance to plasticiser migration and is suitable for use over normal underfloor heating installations.

USES

JM500 can be used to install the following:

Hard/Resilient Floorcoverings:

Vinyls: Sheet, tiles, cushion and other vinyl backed floorcoverings including mineral felt backed vinyls.

Carpets: PVC backed, polyurethane foam backed and many other carpets and needlepunch / fibrebonded carpets where a solvent free system is specified.

SUBFLOORS/WALLS

Suitable subfloors include concrete, sand/cement screed, smoothing underlayment, plyboard, flooring grade chipboard, hardboard, wood and existing well bonded resilient flooring.

****There are certain grades of floor/wall board that have been treated with paraffin wax to provide a waterproof quality. There are also other types of floor/wall boards in use that have been treated, eg.. Moisture proofing, preservatives and fire retardants. These types of boards are not suitable with this adhesive. Please always check the floor/wall board in use at each installation. Please contact our office for technical information.**

With existing well bonded resilient flooring care must be taken to ensure the subfloor under the resilient flooring is sound and the surface of the resilient flooring is thoroughly cleaned of any polish etc. if this cannot be done, the existing resilient flooring must be removed and the subfloor made good before proceeding.

PREPARATION

All part of the installation should comply with the latest edition of the following British Standard Code of Practice: BS5325 The Installation of Textile Floorcoverings. Subfloors must be sound, smooth, clean, dry and free from any contamination which will effect adhesion. Relative humidity of cementitious subfloors should be 75% or less (when tested by the method described in BS8203). Direct to the earth bases must incorporate an effective damp proof membrane. Underfloor heating must be switched off 48 hours before and after installation. Very absorbent surfaces should be primed with a suitable sealer.

APPLICATION

For the best results a minimum temperature of 18°C (65°F) should be maintained for the installation.

An appropriate V notched trowel should be used to apply the adhesive evenly. For vinyls and other smooth backed floorcoverings a 1.5mm x 5.0mm is recommended, whilst a larger trowel should be selected for floorcoverings with a more profiled back. Trowels should be cleaned after use with water whilst the adhesive is still wet.

Apply the adhesive evenly to an area of such size that the floorcovering can be laid whilst the adhesive is receptive and gives good transfer. On absorbent surfaces lay the floorcovering immediately or in the case of tiles after 10-15 minutes (this reduces the slip). On non-absorbent surfaces allow the adhesive to develop a tack or, for sheet goods, employ a "double drop" technique to reduce the waiting time before laying.

To reduce the effect of shadowing on some vinyls, it is recommended that the adhesive is smoothed out whilst wet with a paint roller that has been pre-wetted with adhesive. Once installation area is laid, roll immediately in two directions (at right angles to each other) with a 68kg roller (on carpets use a weighted glider). This is to remove any trapped air and ensure good all over adhesive contact. A second rolling (or gliding) is recommended approximately 1 hour later to ensure a strong bond is established.

HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given.

Ensure area of use is well ventilated.

Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves.

In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help.

If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.

TECHNICAL SPECIFICATION

PRODUCT CODE—JM500

PRODUCT NAME—Acrylic Adhesive

CONTAINER SIZE—5kg & 15kg Plastic Buckets

TYPE—Acrylic Emulsion

COLOUR—Off White

VISCOSITY—Approx 45,000 cps at 20°C—trowel application

COVERAGE—Between 3m² - 4m² per kilo depending on trowel used & absorbency of subfloor

OPEN TIME—Up to 1 hour depending on temperature, humidity, subfloor porosity and trowel used.

STORAGE—Store between temperatures of 5°C and 30°C

SHELF LIFE—12 months in unopened containers, stored in recommended conditions.

CLEANING—Tools should be cleaned with water whilst adhesive is wet. Use hot water or a solvent should the adhesive dry. Do not use on the skin.

Health and Safety Sheets available on request

morleys 
ADHESIVES

Higher Walton Mill, Higher Walton,
Preston PR5 4DJ

Tel. 01772 626700

Fax. 01772 627372

Website. www.morleys2013.co.uk

Email. sales@morleys2013.co.uk