

InstaLay 25 (Plain and Self-Adhesive Products)

TECHNICAL SPECIFICATION

High Performance, Environmentally Friendly, Rubber Crumb Underlays

Domestic and commercial use, suitable for heavy foot traffic

Manufactured using recycled rubber crumb

Guaranteed for 10 Years

Roll Size: 2.5mm - 1.0m x 15.0m (15.0m² / roll) / 3ft 3in x 49ft 2in (161.4ft² / roll)

<u>Specification</u>	<u>BS Requirements</u>	<u>Result</u>	<u>Test Method</u>
Nominal Weight Density Nominal Roll Weight		1.13 kg/m ² / 0.23 lb/ft ² 452 kg/m ³ / 28.2 lb/ft ³ 17 kg / 37.5 lb	
Colour and Appearance Compound Bonding Agent		Black rubber crumb on a non-woven polypropylene backing Recycled tyre tread (minimum 80%) Synthetic Latex	
Odour		No objectionable odour	
Thermal Resistance (R)		0.43 Togs	BS 4745
Acoustic Performance Measured Improvement of Impact Sound (ΔL_w) Impact Insulation Class (IIC)		17dB ΔL_w IIC 49	BS EN ISO 10140-3: 2010 & BS EN ISO 717-2: 2013 ASTM – E492-09, E989-06 & E2179-03

Please Note:

- InstaLay Self-Adhesive products must not be installed at temperatures below 10°C (50°F).
- For further information on the guarantee and product warranty, please refer to the InstaLay guarantee document which is available from the www.instaflor.co.uk website.

Product Codes: IL25, IL25lg & IL25hg	Version: 02	Version Date: 14/04/14	Page 1 of 1
--------------------------------------	-------------	------------------------	-------------